# **SCOPE & DEFINITIONS**

This chapter contains criteria for the storage, handling, and disposition of hazardous materials. It does not cover solid or hazardous waste, underground storage tanks, petroleum storage, and related spill contingency and emergency response requirements. These matters are covered under other chapters. This document does not cover munitions.

**Hazardous Chemical Warning Label** – A label, tag, or marking on a container which provides the following information and which is prepared in accordance with DoD 6050.5-H (DoD Hazardous Chemical Warning Labeling System):

- Identification/name of hazardous chemicals
- Appropriate hazard warnings
- The name and address of the manufacturer, importer or other responsible party

**Hazardous Material** – Any substance, compound, preparation, or material that is capable of posing an unreasonable risk to health, safety, or environment if improperly handled, stored, issued, transported, labeled, or disposed because it displays a characteristic listed in Table 5.1 (Typical Hazardous Materials Characteristics) or the material is listed in Appendix A. Munitions are excluded.

**Hazardous Material Information System (HMIS)** – The computer-based information system developed to accumulate, maintain, and disseminate important information on hazardous material used by DoD. The HMIS has been assigned Report Control Symbol DD-A&T(AR) 1486 in accordance with DoD 8910-M.

**Hazardous Material Shipment** – Any movement of hazardous material in a DoD land vehicle either from an installation to a final destination off the installation, or from a point of origin off the installation to a final destination on the installation, in excess of any of the following quantities:

- For hazardous material identified as a result of inclusion in Appendix A, any quantity in excess of the reportable quantity listed in Appendix A
- For other liquid or semi-liquid hazardous material, in excess of 410 liters (110 gallons)
- For other solid hazardous material, in excess of 225 kg (500 pounds)
- For combinations of liquid, semi-liquid and solid hazardous materials, in excess of 340 kg (750 pounds)

**Local National** – An employee hired under Greek employment conditions.

Material Safety Data Sheet (MSDS) – A form used by manufacturers of chemical products to communicate to users the chemical, physical, and hazardous properties of their product.

FGS Greece 6 November 2002 5-1

# **CRITERIA**

### C5.1 STORAGE AND HANDLING OF HAZARDOUS MATERIALS

Storage and handling of hazardous materials will adhere to DoD Component policies, including Joint Service Publication on Storage and Handling of Hazardous Materials. DLAI 4145.11, TM 38-410, NAVSUP PUB 573, AFJMAN 23-209, and MCO 4450-12.A provide additional guidance on the storage and handling of hazardous materials. The International Maritime Dangerous Goods (IMDG) Code and appropriate DoD and Component instructions provide requirements for international maritime transport of hazardous materials originating from DoD installations. International air shipments of hazardous materials originating from DoD installations are subject to International Civil Air Organization Rules or DoD Component guidance including AFJM 24-204, TM 38-250, NAVSUP 505, MCO P4030.19E, and DLAM 4145.3.

### C5.2 HAZARDOUS MATERIAL DISPENSING AREAS

Hazardous material dispensing areas will be properly maintained. Drums/containers must not be leaking. Drip pans/absorbent materials will be placed under containers as necessary to collect drips or spills. Container contents will be clearly marked. Dispensing areas will be located away from catch basins and storm drains. Appropriate chemical warning signs will be posted for each hazardous material stored in the area. Hazardous material MSDSs will be reviewed to determine whether additional handling and storage requirements are required for a specific chemical.

#### C5.3 HAZARDOUS MATERIAL SHIPMENT

Installations will ensure that for each hazardous material shipment transported on Greek public roads:

- C5.3.1 The shipment is accompanied throughout by shipping papers that clearly describe the quantity and identity of the material and that include an MSDS. The shipment papers must include the ADR accident instruction sheets. The accident instruction sheets should include the following information:
  - Name of the hazardous material, class, and identification number, and a brief description of the physical state (including color and associated odors)
  - Associated risk (primary, secondary, and risks for the environment)
  - Type of personal protective equipment to be used
  - Immediate response measures to be taken by the driver in the event of an accident
  - Spill containment measures to be taken by the driver in the event of leaks or spills
  - Indication of hazardous materials that react with water

- First aid measures
- Any additional information considered necessary for the material in transport
- C5.3.2 All Local National drivers must be ADR certified at an authorized training center; U.S. military drivers must also be ADR trained (see C5.10). All drivers must be briefed on the hazardous material included in the shipment, including health risks of exposure and the physical hazards of the material (including potential for fire, explosion, and reactivity).
- C5.3.3 All drivers will be trained on spill control, use of the accident instruction sheets (see C5.3.1), and emergency notification procedures. Notification procedures are established in Chapter 18.
- C5.3.4 For any hazardous material categorized on the basis of Appendix A, the shipping papers and briefing for the driver must include identification of the material's hazardous properties.
- C5.3.5 The vehicles are subjected to a walk-around inspection by supervisory personnel before and after the material is loaded.
- C5.3.6 Packages are labeled in accordance with Joint Service Publications (see C5.1), C5.7, and Table 5.2. The Joint Service Publications incorporate requirements for UN standard packaging.
- C5.3.7 If a commercial transporter is used, contracting officials will ensure that the transporter has the applicable licenses or permits for operation in Greece.

### C5.4 MASTER LISTING OF STORAGE LOCATIONS & INVENTORY OF MATERIAL

Each installation will maintain a master listing of all storage locations for hazardous material and an inventory of all hazardous materials contained therein (see C18.2.1.4).

### C5.5 MATERIAL SAFETY DATA SHEETS

Each material safety data sheet (MSDS) shall be in English and Greek if Local National workers are present in the work place, and shall contain at least the following information. If a translated MSDS is not available, bilingual training will be provided on the content of the MSDS.

- C5.5.1 The identity used on the label:
  - C5.5.1.1 If the hazardous chemical is a single substance, its chemical and common name, and its Chemical Abstract Service (CAS) Number.

C5.5.1.2 If the hazardous chemical is a mixture which has been tested as a whole to determine its hazards, the chemical and common name(s) of the ingredients which contribute to these known hazards, and the common name(s) of the mixture itself; or,

- C5.5.1.3 If the hazardous chemical is a mixture which has not been tested as a whole:
  - C5.5.1.3.1 The chemical and common name(s) of all ingredients which have been determined to be health hazards, and which comprise 1% or greater of the composition, except that chemicals identified as carcinogens shall be listed if the concentrations are 0.1% or greater
  - C5.5.1.3.2 The chemical and common name(s) of all ingredients which have been determined to be health hazards, and which comprise less than 1% (0.1% for carcinogens) of the mixture, if there is evidence that the ingredient(s) could be released from the mixture in concentrations which would exceed an established OSHA permissible exposure limit, or could present a health hazard to employees
  - C5.5.1.3.3 The chemical and common name(s) of all ingredients which have been determined to present a physical hazard when present in the mixture
- C5.5.2 Physical and chemical characteristics of the hazardous chemical (such as vapor pressure, flash point)
- C5.5.3 The physical hazards of the hazardous chemical, including the potential for fire, explosion, and reactivity
- C5.5.4 The health hazards of the hazardous chemical, including signs and symptoms of exposure, and any medical conditions which are generally recognized as being aggravated by exposure to the chemical
- C5.5.5 The primary route(s) of entry (inhalation, skin absorption, ingestion, etc.)
- C5.5.6 The appropriate occupational exposure limit recommended by the chemical manufacturer, importer, or employer preparing the MSDS, where available
- C5.5.7 Whether the hazardous chemical has been found to be a potential carcinogen
- C5.5.8 Any generally applicable precautions for safe handling and use which are known to the chemical manufacturer, importer, or employer preparing the MSDS, including appropriate hygienic practices, protective measures during repair and maintenance of contaminated equipment, and procedures for clean-up of spills and leaks

C5.5.9 Any generally applicable control measures which are known to the chemical manufacturer, importer, or employer preparing the MSDS, such as appropriate engineering controls, work practices, or personal protective equipment

- C5.5.10 Emergency and first aid procedures
- C5.5.11 The date of preparation of the MSDS or the last change to it
- C5.5.12 The name, address, and telephone number of the chemical manufacturer, importer, employer, or other responsible party preparing or distributing the MSDS, who can provide additional information on the hazardous chemical and appropriate emergency procedures, if necessary

#### C5.6 MSDS FILE

Each work center will maintain a file of MSDS for each hazardous material procured, stored, or used at the work center. MSDSs that are not contained in the HMIS and those MSDSs prepared for locally purchased items should be incorporated into HMIS. A file of MSDS information not contained in HMIS should be maintained on site.

### C5.7 HAZARDOUS CHEMICAL WARNING LABELS

All hazardous materials on DoD installations will have a Hazardous Chemical Warning Label in accordance with DoDI 6050.5-H and have MSDS information either available or in HMIS in accordance with DoD Directive 6050.1 and other Component instructions. These requirements apply throughout the lifecycle of these materials.

All hazardous materials labels must be in English and Greek if Local National workers are present in the workplace and must follow the requirements in Table 5.2. If a translated label is not available, bilingual training will be provided on the content of the label.

### C5.8 REDUCTION OF THE USE OF HAZARDOUS MATERIAL

DoD installations will reduce the use of hazardous materials where practical through resource recovery, recycling, source reduction, acquisition, or other minimization strategies in accordance with Service guidance on improved hazardous material management processes and techniques.

### C5.9 EXCESS HAZARDOUS MATERIAL

All excess hazardous material will be processed through the Defense Reutilization and Marketing Service (DRMS) in accordance with the procedures in DoD 4160.21-M. DRMS will only donate, transfer, or sell hazardous material to environmentally responsible parties. Prior to doing so, DRMS should evaluate whether there are restrictions on the marketing or distribution of that material within Greece. Materials that are transferred to a third party should be labeled in

FGS Greece 6 November 2002 5-5

accordance with C5.7. This criterion is not intended to prohibit the transfer of usable hazardous material between DoD activities participating in a regional or local pharmacy or exchange program.

### C5.10 PERSONNEL TRAINING

All personnel who use, handle, or store hazardous materials will be trained in accordance with DoDI 6050.5 (DoD Hazard Communication Program) and other Component instructions. The training will be documented and the training records will be retained in accordance with applicable instructions. At a minimum, the training will include the following subjects:

- Hazards to which the personnel are potentially exposed
- Precautions for safe use of the hazardous material
- Personal protective equipment and control devices
- Exposure symptoms and emergency first aid treatment
- The use of MSDSs
- Labeling of hazardous materials in accordance with C5.7 and DoDI 6050.5-H
- Waste disposal instructions

All U.S. military personnel who transport hazardous material by vehicle will also be trained in accordance with ADR. Local National employees who transport hazardous material by vehicle must be ADR trained and certified by an authorized training center. Local National employees who transport hazardous material by tank trucks must receive specific ADR training for tank truck transportation.

### C5.11 PREVENTION OF UNAUTHORIZED ENTRY

The installation must prevent the unauthorized entry of persons or livestock into the hazardous materials storage area.

# **ADMINISTRATIVE ITEMS**

None identified.

## Table 5.1 – Typical Hazardous Materials Characteristics

- The item is a health or physical hazard. Health hazards include carcinogens, corrosive materials, irritants, sensitizers, toxic materials, and materials which damage the skin, eyes, or internal organs. Physical hazards include combustible liquids, compressed gasses, explosives, flammable materials, organic peroxides, oxidizers, pyrophoric materials, unstable (reactive) materials and water-reactive materials.
- 2. The item and/or its disposal is regulated by the host nation because of its hazardous nature.
- 3. The item contains asbestos, mercury, or polychlorinated biphenyls.
- 4. The item has a flashpoint below 93°C (200°F) closed cup, or is subject to spontaneous heating or is subject to polymerization with release of large amounts of energy when handled, stored, and shipped without adequate control.
- 5. The item is a flammable solid or is an oxidizer or is a strong oxidizing or reducing agent with a standard reduction potential of greater than 1.0 volt or less than -1.0 volt.
- 6. In the course of normal operations, accidents, leaks, or spills, the item may produce dusts, gases, fumes, vapors, mists, or smokes with one or more of the above characteristics.
- 7. The item has special characteristics that in the opinion of the manufacturer or the DoD Components could cause harm to personnel if used or stored improperly.

## Table 5.2 – Labeling Requirements for Hazardous Materials in the Workplace

Hazardous materials must be labeled in English and Greek if Local National workers are present in the workplace (see C5.7). The Greek text cannot be smaller than the text of any other language, and must contain the following information:

- Name of the material
- Full name, address, and telephone number of the marketer in the EU
- Hazard symbol and specification (printed in black on a yellow-orange background); the color of the product label must be such that the hazard symbol is clearly visible
- The risk (R-) phrases specific for the use and handling of that material (if the quantity exceeds 125 ml)
- The safety (S-) phrases specific for the use and handling of that material (if the quantity exceeds 125 ml)
- The European Inventory of Existing Commercial Substances (EINECS) number, if available
- The EINECS label, if required

The label must be securely placed on one or more sides of the package, to guarantee horizontal reading when the package is stored in its normal position. The dimensions of labels must be:

Container	Minimum Dimensions for Labels	
Capacity	mm	inches
≤ to 3 liters	52 x 74	1.77 x 2.51
> 3 liters and < to 50 liters	74 x 105	2.51 x 3.57
> 50 liter and < 500 liters	105 x 148	3.57 x 5.03
> 500 liters	148 x 210	5.03 x 7.13

During use within the workplace, hazardous material containers must bear the original manufacturer's label or the Hazardous Chemical Warning Label. If the manufacturer's label does not include the information required by the Hazardous Chemical Warning Label, the container should be labeled in accordance with DoDI 6050.5-H.